



## PN 250

Pressione max esercizio bar	Tipo Type	Size	B	E	O	F	P	S	T	OR
										O-RINGS
210	C.2516 S	1/2"	12,5	6,7	30,2	16,5	24	12	35	4075
	C.2517 S					17,6				
210	C.2520 S	3/4"	15	6,7	38,1	20,5	31,5	13	40	4100
	C.2521 S					21,7				
210	C.2525 S	1"	20	8	44,4	25,5	38	14	45	4131
	C.2527 S					27,3				
210	C.2530 S	1" 1/4	25	8	50,8	30,5	43	16	50	4150
	C.2532 S					32,5				
	C.2534 S					34,2				
210	C.2538 S	1" 1/2	32	8	60,3	38,5	50	18	55	4187
	C.2540 S					40,7				
175	C.2543 S	2"	38	9,5	71,4	43	62	20	65	4225
210	C.2549 S					49				
250	C.2550 S	2"	38	9,5	71,4	50,7	62	20	65	4225
	C.2561 S.25					61				
250	C.2564 S.25	2" 1/2	47	12	87,2	64	76	22	70	4275
	C.2574 S.25					74				
250	C.2577 S.25	3"	58	15	101,6	77	90	24	80	4337
	C.2581 S.25					81				
250	C.2591 S.25	4"	70	23,5	131	91	114	28	105	6350

Per ordinare coduli  
How to order straight adaptors  
Example pour commander collets  
Bestellbeispiel für gerade adaptoren

Es.: C.....S A  
Es.: C.....S B