



Serie 3000 psi

Pressione max esercizio bar	Tipo Type	S.A.E.	A	B	C	D	S	G Viti / Bolts		H	I	L	M
								Metr.	UNC				
348	C. 080-ST-F-F	3/8"	17,5	10	36	16	3,7	M 8	5/16"	57	38,1	47	17,5
348	C. 080-ST-F-F	1/2"	21,6	13	36	16	4,3	M 8	5/16"	57	38,1	47	17,5
348	C. 100-ST-F-F	3/4"	27,2	19	36	18	4,1	M10	3/8"	66	47,6	49	22,3
348	C. 102-ST-F-F	1"	34,5	25	38	18	4,7	M10	3/8"	71	52,4	53	26,2
278	C. 104-ST-F-F	1 1/4"	42,8	31	41	21	6	M10	7/16"	80	58,7	69	30,2
210	C. 106-ST-F-F	1 1/2"	48,6	38	44	25	5,3	M12	1/2"	94	69,9	77	35,7
210	C. 108-ST-F-F	2"	61	50	45	25	5,5	M12	1/2"	103	77,8	89	42,9
175	C. 110-ST-F-F	2 1/2"	76,6	63	50	25	6,8	M12	1/2"	115	88,9	101	50,8
138	C. 112-ST-F-F	3"	89	73	50	27	8	M16	5/8"	135	106,4	124	61,9
35	C. 114-ST-F-F	3 1/2"	103	89	50	27	7	M16	5/8"	153	120,7	137	69,9
35	C. 116-ST-F-F	4"	115	99	50	27	8	M16	5/8"	163	130,2	147	77,8
35	C. 118-ST-F-F	5"	141	120	50	28	10,5	M16	5/8"	184	152,4	180	92,1

Serie 6000 psi

Pressione max esercizio bar	Tipo Type	A S.A.E.	A	B	C	D	S	G Viti / Bolts		H	I	L	M
								Metr.	UNC				
420	C. 401-ST-F-F	3/8"	17,5	10	36	16	3,7	M 8	5/16"	57	40,5	47	18,2
420	C. 401-ST-F-F	1/2"	21,6	13	36	16	4,3	M 8	5/16"	57	40,5	47	18,2
420	C. 402-ST-F-F	3/4"	27,2	18	36	19	4,6	M 10	3/8"	71	50,8	53	23,8
420	C. 403-ST-F-F	1"	34,5	22	44	24	6,3	M 12	7/16"	80	57,2	66	27,8
420	C. 404-ST-F-F	1 1/4"	42,8	28	44	27	7,4	M 14	1/2"	94	66,6	77	31,8
420	C. 405-ST-F-F	1 1/2"	48,6	32	51	30	8,3	M 16	5/8"	106	79,3	89	36,5
420	C. 406-ST-F-F	2"	61	41	70	37	10	M 20	3/4"	135	96,8	116	44,5
420	C. 408-ST-F-F	2 1/2"	76,6	50	75	45	13	M 24	-	166	123,8	150	58,7
420	C. 410-ST-F-F	3"	90	58	90	55	16	M 30	-	208	152,4	178	71,4

Per ordinazione flange: / Ordering Examples: / Pour commander brides: / Bestellbeispiel für Flansche:

Controflangia con fori fissaggio filettati metriciC...ST-F-F
 Counter flange with metric tapholesC...ST-F-F
 Contre bride avec trous taraudés metriquesC...ST-F-F
 Gegenflansch mit Metrischen Gewindebohrungen ...C...ST-F-F

Controflangia con fori fissaggio filettati UNCU-C...ST-F-F
 Counter flange with UNC tapholesU-C...ST-F-F
 Contre bride avec trous taraudés UNCU-C...ST-F-F
 Gegenflansch mit UNC Gewindebohrungen ...U-C...ST-F-F

Indicare quota "S"
 Specify "S" dimension
 Indiquer quote "S"
 Bestimmen "S" Abmessung