



Serie 3000 psi

| Pressione max esercizio bar | Tipo Type | Size S.A.E. | A | K | I | E | H | M | N | S | OR O-RINGS |
|-----------------------------|---------------|-------------|------|------|----|-----|----|----|----|-----|------------|
| 210 | C.3001-90°-ST | 1/2" | 21,6 | 30,2 | 13 | 6,7 | 22 | 44 | 50 | 4,3 | 4075 |
| 210 | C.3002-90°-ST | 3/4" | 27,2 | 38,1 | 19 | 6,7 | 27 | 53 | 64 | 4,1 | 4100 |
| 210 | C.3003-90°-ST | 1" | 34,5 | 44,4 | 25 | 8 | 34 | 60 | 65 | 4,7 | 4131 |
| 210 | C.3004-90°-ST | 1" 1/4 | 42,8 | 50,8 | 30 | 8 | 42 | 55 | 64 | 6,4 | 4150 |
| 210 | C.3005-90°-ST | 1" 1/2 | 48,6 | 60,3 | 38 | 8 | 50 | 66 | 78 | 5,3 | 4187 |

Serie 6000 psi

| Pressione max esercizio bar | Tipo Type | Size S.A.E. | A | K | I | E | H | M | N | S | OR O-RINGS |
|-----------------------------|---------------|-------------|------|------|----|------|----|----|----|-----|------------|
| 420 | C.6001-90°-ST | 1/2" | 21,6 | 31,8 | 13 | 7,7 | 22 | 44 | 50 | 4,3 | 4075 |
| 420 | C.6002-90°-ST | 3/4" | 27,2 | 41,3 | 19 | 8,7 | 27 | 53 | 64 | 4,6 | 4100 |
| 420 | C.6003-90°-ST | 1" | 34,5 | 47,6 | 22 | 9,5 | 34 | 60 | 62 | 6,3 | 4131 |
| 420 | C.6004-90°-ST | 1" 1/4 | 42,8 | 54 | 28 | 10,3 | 42 | 70 | 72 | 7,4 | 4150 |
| 420 | C.6005-90°-ST | 1" 1/2 | 48,6 | 63,5 | 32 | 12,5 | 50 | 80 | 84 | 8,3 | 4187 |

Per ordinazione flange (Indicare quota "S"):
 Ordering Examples (Specify "S" dimension):
 Pour commander brides (Indiquer quote "S"):
 Bestellbeispiel für Flansche (Bestimmung "S" Abmessung): C.....90°-ST A