



CERT

# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DG-4314CP0497**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Officine Meccaniche Ciocca S.p.A. Via Treviglio, 44, I-24053 Brignano Gera d'Adda (BG)
<b>Distributor</b> <i>Vertreiber</i>	Officine Meccaniche Ciocca S.p.A. Via Treviglio, 44, I-24053 Brignano Gera d'Adda (BG)
<b>Product Category</b> <i>Produktart</i>	gas fittings: Shut-off valve for gas transmission >PN 16 (4314)
<b>Product Description</b> <i>Produktbezeichnung</i>	Ball-valve for installation in function pipes for equipment according to DVGW-working sheets G 491 and G 492
<b>Model</b> <i>Modell</i>	CRH- ...
<b>Test Reports</b> <i>Prüfberichte</i>	laboratory control test: 15/1166/4314/150 from 23.09.2015 (EBI)
<b>Test Basis</b> <i>Prüfgrundlagen</i>	DVGW VP 308 (01.09.2004) DIN EN 14141 (01.08.2013)

**Date of Expiry / File No.** 10.09.2020 / 17-0377-GNV  
**Ablaufdatum / Aktenzeichen**

70008-04-A-DE

06.06.2017 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body  
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



Deutsche  
Akkreditierungsstelle  
D-ZE-16028-01-05

DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

<b>Gas Category</b> <i>Gasart</i>	<b>Remarks</b> <i>Bemerkungen</i>
fuel gases according to G260	

<b>Type</b> <i>Typ</i>	<b>Technical Data</b> <i>Technische Daten</i>	<b>Remarks</b> <i>Bemerkungen</i>
CRH-...	nominal pressure rating: MOP 16/250 nominal diameter: DN 6	
CRH-...	nominal pressure rating: MOP 16/250 nominal diameter: DN 8	
CRH-...	nominal pressure rating: MOP 16/250 nominal diameter: DN 10	
CRH-...	nominal pressure rating: MOP 16/250 nominal diameter: DN 12	
CRH-...	nominal pressure rating: MOP 16/250 nominal diameter: DN 16	
CRH-...	nominal pressure rating: MOP 16/250 nominal diameter: DN 20	
CRH-...	nominal pressure rating: MOP 16/250 nominal diameter: DN 25	

<b>Type Variation</b> <i>Ausführungsvariante</i>	<b>Explanations</b> <i>Erläuterungen</i>
...EL	type of connection: solderless fittings according to DIN 2353, light serie
...ES	type of connection: solderless fittings according to DIN 2353, heavy serie
...R	type of connection: internal thread Rp 1/8 ... Rp 1 according to DIN EN 10226-1, maximum operation pressure: 16 bar (MOP 16)

**certified Components**  
*zertifizierte Bauteile / Werkstoffe*

<b>Registr. No.</b> <i>Registrier-Nr.</i>	<b>Component</b> <i>Bauteil (Produktart)</i>	<b>Model/Type</b> <i>Modell/Typ</i>	<b>Manufacturer</b> <i>Hersteller</i>
NG-5112AR0799	Sealing material made of elastomers for gas appliances	0170 NBR 70/0170 NBR 70	AR-TEX S.p.A.

<b>Hints of Utilization / Remarks</b> <i>Verwendungshinweise / Bemerkungen</i>
ambient temperature range: -20...+60 °C