



Serie 250 bar

Pressione max esercizio bar	Tipo Type	Size	B	E	F	P	O	T	OR
									O-RINGS
250	CR.2221-ST	1/2"	10	30,2	6,7	24	18	45	4075
250	CR.2227-ST	3/4"	13	38,1	6,7	31,5	22	50	4100
250	CR.2233-ST	1"	19	44,4	8	38	28	55	4131
250	CR.2242-ST	1" 1/4	25	50,8	8	43	35	60	4150
250	CR.2249-ST	1" 1/2	31	60,3	8	50	43	65	4187
250	CR.2260-ST	2"	38	71,4	9,5	62	50	70	4225
250	CR.2275-ST	2" 1/2	47	87,2	12	76	62	75	4275
250	CR.2290-ST	3"	58	101,6	15	90	76	85	4337
250	CR.2203-ST	3" 1/2	70	119	20	102	90	90	6337
250	CR.2215-ST	4"	80	131	23,5	114	102	105	6387

Serie 400 bar

Pressione max esercizio bar	Tipo Type	Size	B	E	F	P	O	T	OR
									O-RINGS
400	CR.4221-ST	1/2"	10	31,8	7,7	24	18	45	4075
400	CR.4227-ST	3/4"	13	39,5	8,7	32	22	50	4100
400	CR.4233-ST	1"	18	47,6	9,5	38	28	55	4131
400	CR.4242-ST	1" 1/4	22	54	10,3	44	35	60	4150
400	CR.4249-ST	1" 1/2	29	63,5	12,5	51	44	65	4187
400	CR.4260-ST	2"	35	79,4	12,5	67	51	70	4225
400	CR.4275-ST	2" 1/2	43	94,2	16,5	80	61	80	6275
400	CR.4290-ST	3"	53	104	18	90	80	90	6300
400	CR.4203-ST	3" 1/2	58	119	20	102	90	90	6337
400	CR.4215-ST	4"	63	131	23,5	114	102	105	6350

Per ordinare coduli
How to order straight adaptors
Example pour commander collets
Bestellbeispiel für gerade adaptoren

Es.: CR.....ST-A
Es.: CR.....ST-B