



### Serie 3000 psi

| Pressione max esercizio bar | Tipo Type    | A     | S.A.E. | B   | C  | D  | E  | F  | G Viti / Bolts |       | H   | I     | L   | M    | OR O-RING |
|-----------------------------|--------------|-------|--------|-----|----|----|----|----|----------------|-------|-----|-------|-----|------|-----------|
|                             |              |       |        |     |    |    |    |    | Metr.          | UNC   |     |       |     |      |           |
| 348                         | C.F.S. 080-S | 17,5  | 3/8"   | 13  | 36 | 16 | 18 | 14 | M 8            | 5/16" | 57  | 38,1  | 47  | 17,5 | 4075      |
| 348                         | C.F.S. 080-S | 21,6  | 1/2"   | 13  | 36 | 16 | 18 | 14 | M 8            | 5/16" | 57  | 38,1  | 47  | 17,5 | 4075      |
| 348                         | C.F.S. 100-S | 27,2  | 3/4"   | 19  | 36 | 18 | 18 | 16 | M10            | 3/8"  | 66  | 47,6  | 49  | 22,3 | 4100      |
| 348                         | C.F.S. 102-S | 34,1  | 1"     | 25  | 38 | 18 | 18 | 16 | M10            | 3/8"  | 70  | 52,4  | 53  | 26,2 | 4131      |
| 278                         | C.F.S. 104-S | 42,8  | 1 1/4" | 31  | 41 | 21 | 20 | 18 | M10            | 7/16" | 80  | 58,7  | 69  | 30,2 | 4150      |
| 210                         | C.F.S. 106-S | 48,6  | 1 1/2" | 38  | 44 | 25 | 22 | 18 | M12            | 1/2"  | 94  | 69,9  | 77  | 35,7 | 4187      |
| 210                         | C.F.S. 108-S | 61    | 2"     | 50  | 45 | 25 | 24 | 18 | M12            | 1/2"  | 103 | 77,8  | 89  | 42,9 | 4225      |
| 175                         | C.F.S. 110-S | 76,6  | 2 1/2" | 63  | 50 | 25 | 28 | 18 | M12            | 1/2"  | 115 | 88,9  | 101 | 50,8 | 4275      |
| 138                         | C.F.S. 112-S | 90,5  | 3"     | 73  | 50 | 27 | 28 | 25 | M16            | 5/8"  | 135 | 106,4 | 124 | 61,9 | 4337      |
| 35                          | C.F.S. 114-S | 103   | 3 1/2" | 89  | 50 | 27 | 28 | 25 | M16            | 5/8"  | 153 | 120,7 | 136 | 69,9 | 4387      |
| 35                          | C.F.S. 116-S | 115,3 | 4"     | 99  | 50 | 27 | 28 | 25 | M16            | 5/8"  | 163 | 130,2 | 147 | 77,8 | 4437      |
| 35                          | C.F.S. 118-S | 142   | 5"     | 120 | 50 | 28 | 28 | 25 | M16            | 5/8"  | 184 | 152,4 | 180 | 92,1 | 4537      |

### Serie 6000 psi

| Pressione max esercizio bar | Tipo Type        | A    | S.A.E. | B  | C  | D  | E  | F  | G Viti / Bolts |       | H   | I     | L   | M    | OR O-RING |
|-----------------------------|------------------|------|--------|----|----|----|----|----|----------------|-------|-----|-------|-----|------|-----------|
|                             |                  |      |        |    |    |    |    |    | Metr.          | UNC   |     |       |     |      |           |
| 420                         | C.F.S. 401-S     | 17,5 | 3/8"   | 13 | 36 | 16 | 18 | 14 | M 8            | 5/16" | 57  | 40,5  | 47  | 18,2 | 4075      |
| 420                         | C.F.S. 401-S     | 21,6 | 1/2"   | 13 | 36 | 16 | 18 | 14 | M 8            | 5/16" | 57  | 40,5  | 47  | 18,2 | 4075      |
| 420                         | C.F.S. 402-S     | 27,2 | 3/4"   | 19 | 36 | 19 | 20 | 16 | M 10           | 3/8"  | 71  | 50,8  | 53  | 23,8 | 4100      |
| 420                         | C.F.S. 403-S     | 34,1 | 1"     | 25 | 44 | 24 | 22 | 19 | M 12           | 7/16" | 80  | 57,2  | 66  | 27,8 | 4131      |
| 420                         | C.F.S. 404-S     | 42,8 | 1 1/4" | 31 | 44 | 27 | 22 | 22 | M 14           | -     | 94  | 66,6  | 77  | 31,8 | 4150      |
| 420                         | C.F.S. 404-SF133 | 42,8 | 1 1/4" | 31 | 44 | 27 | 22 | 22 | M 12           | 1/2"  | 94  | 66,6  | 77  | 31,8 | 4150      |
| 420                         | C.F.S. 405-S     | 48,6 | 1 1/2" | 38 | 51 | 30 | 24 | 24 | M 16           | 5/8"  | 106 | 79,3  | 89  | 36,5 | 4187      |
| 420                         | C.F.S. 406-S     | 61   | 2"     | 50 | 70 | 37 | 25 | 32 | M 20           | 3/4"  | 135 | 96,8  | 116 | 44,5 | 4225      |
| 420                         | C.F.S. 408-S     | 76,6 | 2 1/2" | 63 | 75 | 45 | 28 | 40 | M 24           | -     | 166 | 123,8 | 150 | 58,7 | 4275      |
| 420                         | C.F.S. 410-S     | 90,5 | 3"     | 73 | 90 | 55 | 30 | 55 | M 30           | -     | 208 | 152,4 | 178 | 71,4 | 4337      |

Per ordinazione flange: / Ordering Examples: / Pour commander brides: / Bestellbeispiel für Flansche:

Solo flangia .....CFS...S  
Only flange .....CFS...S  
Seulement bride ...CFS...S  
Nur Flansch .....CFS...S

Flangia completa di viti UNC, rondelle e OR .....CFS...S-U  
Complete flange with UNC screws, washers and o-ring .....CFS...S-U  
Bride complete des vis UNC, rondelles et OR .....CFS...S-U  
Flansch einschl. UNC-Schrauben, Federringen und O-Ring ...CFS...S-U

Flangia completa di viti metriche, rondelle e OR .....CFS...S-M  
Complete flange with metrical screws, washers and o-ring .....CFS...S-M  
Bride complete des vis métriques, rondelles et OR .....CFS...S-M  
Flansch einschl. metrischen Zylinderschrauben, Federringen und O-Ring ...CFS...S-M