



Serie 250 bar

Pressione max esercizio bar	Tipo Type	Size	B	C	D		E	H	I		I		OR O-RINGS
					CETOP	SID			CETOP	SID	CETOP	SID	
250	O.27017	3/8"	12	16	7	7	40	23	24,7	24,7	M 6 x 25	M 6 x 25	3068
250	O.27021	1/2"	14	23	9	7	45	32	29,7	30	M 8 x 35	M 6 x 30	4075
250	O.27027	3/4"	19	23	9	9	50	32	35,3	35,3	M 8 x 35	M 8 x 35	4100
250	O.27034	1"	25	24	11	11	65	35	43,8	43,8	M10 x 40	M10 x 40	4131
250	O.27042	1" 1/4	30	25	13	13	75	38	51,6	51,6	M12 x 45	M12 x 40	4150
250	O.27049	1" 1/2	36	27	15	13	85	42	60	60	M14 x 50	M12 x 50	4187
250	O.27060	2"	45	27	17	15	100	44	69,4	68	M16 x 55	M14 x 50	4225
250	O.27075	2" 1/2	58	34	21	19	120	55	83,4	85	M20 x 70	M18 x 70	4275
250	O.27090	3"	60	37	21	23	140	60	102,5	95	M20 x 70	M22 x 70	4337
250	O.27115	4"	70	35	25	-	160	60	113,2	-	M24 x 80	-	6425

Serie 400 bar

Pressione max esercizio bar	Tipo Type	Size	B	C	D	E	H	I	I	OR O-RINGS
400	O.47021	1/2"	14	23	9	45	32	29,7	M 8 x 35	4075
400	O.47027	3/4"	19	23	9	50	32	35,3	M 8 x 35	4100
400	O.47034	1"	25	24	11	65	35	43,8	M10 x 40	4131
400	O.47042	1" 1/4	30	25	13	75	38	51,6	M12 x 45	4150
400	O.47049	1" 1/2	36	27	15	85	42	60	M14 x 50	4187
400	O.47060	2"	45	27	17	100	44	69,4	M16 x 55	4225
400	O.47075	2" 1/2	58	34	21	120	55	83,4	M20 x 70	6275
400	O.47090	3"	60	37	21	140	60	102,5	M20 x 70	6300

Per ordinare le flange, specificare se CETOP o SID
Ordering flanges, specify if CETOP or SID
Pour commander brides, indiquer s'il vous plait si CETOP ou SID
Um Flansche zu bestellen, bitte CETOP oder SID Ausführung angeben

Es.: CETOP O.....AM
Es.: SID O.....AM