



PN 250

Pressione max esercizio bar	Tipo Type	Size	B	E	O	F	P	S	T	OR
										O-RINGS
210	C.2516 S	1/2"	12,5	6,7	30,2	16,5	24	12	35	4075
	C.2517 S					17,6				
210	C.2520 S	3/4"	15	6,7	38,1	20,5	31,5	13	40	4100
	C.2521 S					21,7				
210	C.2525 S	1"	20	8	44,4	25,5	38	14	45	4131
	C.2527 S					27,3				
210	C.2530 S	1" 1/4	25	8	50,8	30,5	43	16	50	4150
	C.2532 S					32,5				
	C.2534 S					34,2				
210	C.2538 S	1" 1/2	32	8	60,3	38,5	50	18	55	4187
	C.2540 S					40,7				
175	C.2543 S					43				
210	C.2549 S	2"	38	9,5	71,4	49	62	20	65	4225
	C.2550 S					50,7				
250	C.2561 S.25	2" 1/2	47	12	87,2	61	76	22	70	4275
	C.2564 S.25					64				
250	C.2574 S.25	3"	58	15	101,6	74	90	24	80	4337
250	C.2577 S.25	3" 1/2	58	20	119	77	102	24	90	6337
	C.2581 S.25					81				
250	C.2591 S.25	4"	70	23,5	131	91	114	28	105	6350

Per ordinare coduli
How to order straight adaptors
Example pour commander collets
Bestellbeispiel für gerade adaptoren

Es.: C.....S A
Es.: C.....S B